

Hydroflex[®] 30

DESCRIPTION

Hydroflex[®]30 is a 2 mm thick modified bitumen separation / protection sheet with a 95 g / sq m reinforcement layer. Both sides are sanded.

BASIC USE

Hydroflex[®]30 is specifically designed to be embedded into Hydrotech's Monolithic Membrane 6125EV roofing and waterproofing membrane to provide protection from typical construction traffic. In high traffic areas where vehicular traffic is anticipated or extreme physical abuse is expected, additional protection may also be required for the membrane assembly.



APPLICATION

To be used as a separation / protection sheet. Apply Hydroflex[®] 30, while the membrane is still hot using pressure with a broom or roller. Lap the joints sufficiently to ensure complete coverage.

TECHNICAL DATA

Type	Mixture of selected bitumen and SBS polymer glass, fleece reinforcement 95 gr/sq m
Form	Roll 1 m x 15 m (15 sq m) , 3.3 ft x 49.2 ft (162 sq ft)
Weight	38.2 kg (84 lbs) approx.
Thickness	2 mm – 2.2 mm (78.7 mil – 86.6 mil)

LEED INFORMATION

	Credit 4	Credit 5
Recycled Content (% by weight)	0	
Manufacture Location		Brampton, Ont.
Extraction/Harvesting Location		N/A
VOC Content (g/L)		0

The contents and methods described herein are the intellectual property of Hydrotech Membrane Corp.. The information is based on data and knowledge considered to be true and correct at the time of publication and is offered for the user's consideration, investigation and verification. The information is subject to change without notice. The determination of suitability and fitness of the products and the application described herein for a particular purpose are the sole responsibility of the user. Please read all statements, recommendations and suggestions in conjunction with the conditions of sale which apply to all goods sold by Hydrotech Membrane Corp., including the express disclaimers by each company of the implied warranties of merchantability or fitness for a particular purpose.