

Flex-Flash FV-14

GENERAL DESCRIPTION

Flex-Flash FV-14 –Polyester SB nonwoven reinforcing fabric.

BASIC USE

For use with Hydrotech Monolithic Membrane 6125® as a vertical reinforcement.



FORM

Available in rolls of :

Width	Length	Qty per package
965 mm (38 in.)	182.8 m (200 yards)	1

PHYSICAL PROPERTIES

Properties	Test Method	Unit	Value
Weight	ASTM D-3776	g/sm (Oz/sq. yard)	34,0 (1,0)
Thickness	ASTM D-1777	Mm (Mils)	0,24 (9,4)
Tensile Strength	ASTM D5035-90	MD	MD 93,4 (21)
		CD	CD 75,6 (17)
Tear Strength	ASTM D-5733-99	MD	MD 24 (5,5)
		CD	CD 29 (6,7)

LEED INFORMATION

	Credit 4	Credit 5
Recycled Content (% by weight)	0	
Manufacture Location		Tennessee, U.S.A.
Extraction/Harvesting Location		N/A
VOC Content (g/L)		

The contents and methods described herein are the intellectual property of Hydrotech Membrane Corp.. The information is based on data and knowledge considered to be true and correct at the time of publication and is offered for the user's consideration, investigation and verification. The information is subject to change without notice. The determination of suitability and fitness of the products and the application described herein for a particular purpose are the sole responsibility of the user. Please read all statements, recommendations and suggestions in conjunction with the conditions of sale which apply to all goods sold by Hydrotech Membrane Corp., including the express disclaimers by each company of the implied warranties of merchantability or fitness for a particular purpose.