

Quick-Set

DESCRIPTION

QUICK-SET is a synthetic rubber based adhesive designed for use with hot applied rubberized asphalt membrane MM6125®. It provides quicker setting and positive adhesion.

BASIC USE

Used as an adhesive for hot applied rubberized asphalt membrane MM6125® when applied to concrete masonry, wood and metal surfaces.



TECHNICAL DATA

COLOR	Blue
SOLID	30% (approx.)
WEIGHT PER LITRE	0.9 kg/liter
COVERAGE	1.6 to 2.5 liters per 10 sq m
DRYING TIME	at 20°C, 50% humidity, 1 hour- touch dry
SERVICE TEMPERATURE	-40°C @ 80°C (-40°F @ 176°F)
FLAMMABILITY	Combustible

INSTALLATION

Apply by brush, roller or spray. Allow Quick-Set to dry before applying membrane, usually 1-2 hours.

LIMITATIONS

Solvent in product attacks polystyrene insulation. Avoid use where solvent odors may be exposed to food or other susceptible products.

PREPARATION

Surface must be dry and free from dust, dirt, grease and other foreign matter.

LEED INFORMATION

	Credit 4	Credit 5
Recycled Content (% by weight)	0	
Manufacture Location		Mirabel, Quebec, Canada
Extraction/Harvesting Location		Hydrocarbon resin: USA Polymer: USA Toluen: USA
VOC Content (g/L)		700

The contents and methods described herein are the intellectual property of Hydrotech Membrane Corp.. The information is based on data and knowledge considered to be true and correct at the time of publication and is offered for the user's consideration, investigation and verification. The information is subject to change without notice. The determination of suitability and fitness of the products and the application described herein for a particular purpose are the sole responsibility of the user. Please read all statements, recommendations and suggestions in conjunction with the conditions of sale which apply to all goods sold by Hydrotech Membrane Corp., including the express disclaimers by each company of the implied warranties of merchantability or fitness for a particular purpose.